CBPEXPORT Ocean Manifest - 355 - Customs Acceptance/Rejection

October 2024





Table of Changes

Revision Number	Date of Change	Section(s) Affected	Brief Description of Change
1.5	10/17/2024	LOOP ID - M13	Updated M13 loop at position 1800/1850 to Not Used
1.5	10/17/2024	LOOP ID - MBL	Updated MBL loop at position 1760/1780 to Not Used
1.4	8/29/2024	M1002	Added O – Containerized and VE – Un- Containerized to Type Code
1.3	4/2024	К3	Added M13 for Total Bills/Arrivals Rejected and Accepted
1.2	7/2023	M1011	Added missing M1011 documentation
1.1	1/2023	Notes	Update to show the correct Appendix J
		M1006	Update to show as Dependent

355 Customs Acceptance/Rejection

Functional Group ID=AZ

Introduction:

This X12 Transaction Set contains the format and establishes the data contents of the Customs Acceptance/Rejection Transaction Set (355) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used by Customs to report errors and discrepancies discovered in the Customs transaction sets to ocean carriers, terminal operators, port authorities and service centers.

This Implementation Guideline uses the ASC X12 6050 Standards Version/Release as its base. The transaction structure has been altered to accommodate U.S. Customs and Border Protection implementation requirements.

Notes:

The TS355 is returned in response to the following inbound X12 messages: 309, 353, 358,

The M10 and P4 are returned in the response from CBP. Additionally, the following "loop header" segments will conditionally be returned in the response message when one or more errors are determined for any segment within that group: LX, M13, M11, N9, N1, N3, N4, PER, M12, M21, M15, M20, VID, VC, N10, H1 and H2.

When one or more error(s) are determined as a result of processing a given transaction, each segment in-error is returned in the response message and is immediately followed by one or more Error segments (K1) describing the nature of the error. All error messages found in the K1 segments are explained in the CAMIR Appendix J.

The Message Acceptance/Rejection segment (K3) provides summary and is included at the end of a response transaction prior to the SE segment.

SPECIAL MESSAGING CONSTRAINTS:

- Limit one Interchange (ISA-IEA) per message transmission. Limit one message Group (GS-GE) per message transmission.
- Limit one message Group (GS-GE) per message transmission.
- Limit one transaction set (ST-SE) of the same Transaction Set (TS) Identifier Code (i.e., 355). Only one is allowed per message transmission.
- Element delimiters used in this transaction will be '*' (asterisk). No blanks between delimiters if element is null.
- Segment delimiters used in this transaction will be one byte with a value of hex '15'.
- A segment delimiter will be the last byte of data in the message transmission data stream.
- Only uppercase AMERICAN ENGLISH alphabetic data will be transmitted.
- ONLY displayable characters found on a standard American English keyboard will be transmitted. Low-values, carriage return characters, or other non-standard characters shall NOT be transmitted.

- 'Not Used' in the left column indicates that a composite or data element will not be used by CBP.
- 'Dep' in the left column indicates that CBP usage of a particular segment or element is Dependent (Conditional) within the CBP application.
- Per the ASC X12 Standard, an 'M' indicates a Mandatory use, 'O' indicates Optional Use and an 'X' indicates a Conditional use.
- CBP requirements may override ASC X12 Standard Mandatory or Conditional usages.
- Maximum allowable message transmission size is 12 megabytes (12,582,912 bytes) of data.

Heading:

M	Pos. <u>No.</u> 0050	Seg. <u>ID</u> ISA	Name Interchange Control Header	Req. <u>Des</u> . M	Max.Use	Loop <u>Repeat</u>	Notes and Comments
M	0075	GS	Functional Group Header	M	1		
M	0100	ST	Transaction Set Header	M	1		
M	0200	M10	Manifest Identifying Information	M	1		
	0300	K1	Remarks	O	10		
			LOOP ID - VEH			1	
Not Used	0310	VEH	Vehicle Information	О	1		
Not Used	0311	K1	Remarks	О	10		
			LOOP ID - M7			1	
Not Used	0320	M7	Seal Numbers	О	1		
Not Used	0321	K1	Remarks	O	10		
			LOOP ID - CII			1	
Not Used	0330	CII	Conveyance Insurance Information	О	1		
Not Used	0331	K1	Remarks	O	10		
			LOOP ID - NM1		-	999	
Not Used	0340	NM1	Individual or Organizational Name	О	1		
Not Used	0341	K1	Remarks	О	10		
			LOOP ID - DMG			1	
Not Used	0350	DMG	Demographic Information	О	1		
Not Used	0351	K1	Remarks	0	10		
			LOOP ID - REF		_	1	
Not Used	0360	REF	Reference Information	О	1		
Not Used	0361	K1	Remarks	О	10		
			LOOP ID - N3			1	
Not Used	0370	N3	Party Location	О	1		
Not Used	0371	K1	Remarks	О	10		
			LOOP ID - N4			1	
Not Used	0380	N4	Geographic Location	О	1		
Not Used	0381	K1	Remarks	О	10		
			LOOP ID - P4			20	<u> </u>
M	0400	P4	Port Information	M	1		
	0500	K1	Remarks	О	10		
			LOOP ID - LX			9999	
	0600	LX	Transaction Set Line Number	О	1		
			LOOP ID - M13			1	
	0700	M13	Manifest Amendment Details	О	1		
	0800	K1	Remarks	O	10		

			LOOP ID - M11			1
	0900	M11	Manifest Bill of Lading Details	О	1	
	1000	K1	Remarks	О	10	
			LOOP ID - N9		-	999
	1050	N9	Extended Reference Information	О	1	,,,
	1070	K1	Remarks	0	10	
	1070	Ki				
			LOOP ID - N1			25
	1100	N1	Party Identification	О	1	
	1200	K1	Remarks	О	10	
			LOOP ID - N3			2
	1300	N3	Party Location	О	1	
	1400	K1	Remarks	О	10	
			LOOP ID - N4			1
	1410	N4	Geographic Location	О	1	
	1420	K1	Remarks	О	10	
			LOOP ID - PER			1
	1440	PER	Administrative Communications Contact	O	1	1
	1440	K1	Remarks	0	10	
	1430	K1		<u> </u>	10	
			LOOP ID - X1			1
Not Used	1470	X1	Export License	О	1	
Not Used	1480	K1	Remarks	О	10	
			LOOP ID - DMG			1
Not Used	1485	DMG	Demographic Information	О	1	
Not Used	1488	K1	Remarks	О	10	
			LOOP ID - M12			9999
Not Used	1500	M12	In-bond Identifying Information	0	1	7777
Not Used	1510	K1	Remarks	0	10	
Not Osca	1310	KI	LOOP ID - R4		10	10
N-4 I I J	1550	D4	Port or Terminal	О	1	10
Not Used	1550	R4	Remarks	0	10	
Not Used	1560	K1		<u> </u>	10	
			LOOP ID - M21			1
Not Used	1570	M21	Supplementary In-Bond Information	О	1	
Not Used	1580	K1	Remarks	О	10	
			LOOP ID - M14			9999
Not Used	1610	M14	General Order Status Information	О	1	
Not Used	1620	K1	Remarks	О	10	
			LOOP ID - M15			9999
	1630	M15	Customs Events Advisory Details	О	1	,,,,
	1640	M15 K1	Remarks	0	10	
	1040	IX1			10	
			LOOP ID - M20			9999
Not Used	1650	M20	Permit to Transfer Request Details	О	1	
Not Used	1680	K1	Remarks	О	10	
			LOOP ID - VID			999
		VID	Conveyance Identification	О	1	
	1700	VID				
	1700 1701	K1	Remarks	О	10	
				0	10	1
			Remarks	0	10	1

	1721	K1	Remarks	О	10	
			LOOP ID - M7A	-	-	1
	1741	M7A	Seal Number Replacement	О	1	
	1751	K1	Remarks	О	1	
			LOOP ID - MBL			9999
Not Used	1760	MBL	Bill of Lading	О	1	
Not Used	1780	K1	Remarks	O	10	
			LOOP ID - M13			999
Not Used	1800	M13	Manifest Amendment Details	O	1	
Not Used	1850	K1	Remarks	О	10	
			LOOP ID - X1			1
Not Used	1870	X1	Export License	О	1	
Not Used	1880	K1	Remarks	О	10	
			LOOP ID - VC	-	_	36
	2000	VC	Motor Vehicle Control	О	1	
	2050	K1	Remarks	О	10	
			LOOP ID - N10	-	-	999
	2100	N10	Quantity and Description	О	1	
	2150	K1	Remarks	O	10	
			LOOP ID - H1			99
	2200	H1	Hazardous Material	О	1	
			LOOP ID - M7A			1
Not Used	2600	M7A	Seal Number Replacement	O	1	
Not Used	2610	K1	Remarks	О	1	
	2300	K1	Remarks	O	10	
			LOOP ID - H2			99
	2400	H2	Additional Hazardous Material Description	О	1	
	2500	K1	Remarks	O	10	

Detail:

	Pos.	Seg.		Req.		Loop	Notes and
	<u>No</u> .	<u>ID</u>	<u>Name</u>	Des.	Max.Use	Repeat	Comments
M	0100	K3	File Information	M	1		
M	0200	SE	Transaction Set Trailer	M	1		
M	0300	GE	Functional Group Trailer	M	1		
M	0400	ΙΕΑ	Interchange Control Trailer	M	1		

Segment: ISA Interchange Control Header

Position: 0050

Loop:

Level: Heading Usage: Mandatory

Max Use: 1

Purpose: To start and identify an interchange of zero or more functional groups and interchange-

related control segments

Syntax Notes: Semantic Notes:

			Data Elem	ent Summary		
M	Ref. <u>Des.</u> ISA01	Data <u>Element</u> I01	<u>Name</u> Authorization Inf	ormation Qualifier e type of information in the Authorization	M	tributes 1 ID 2/2 ation
M	ISA02	I02	interchange sender o	or additional identification or authorization or the data in the interchange; the type of in	M n of the	1 AN 10/10
M	ISA03	103	Always 10 spaces. Security Information	n Information Qualifier (I01) on Qualifier e type of information in the Security Inform	M nation	1 ID 2/2
M	ISA04	104	00 Security Information This is used for iden	ntifying the security information about the n the interchange; the type of information	M e interch	1 AN 10/10 ange
M	ISA05	105	Always 10 spaces. Interchange ID Qua Code indicating the	, ,	M designat	1 ID 2/2 e the
M	ISA06	106	ZZ Interchange Sender Identification code	Mutually Defined r ID published by the sender for other parties t data to them; the sender always codes this Production		
M	ISA07	105	sender or receiver II Always 'ZZ'	system/method of code structure used to on the control of the cont	M designat	1 ID 2/2 e the
M	ISA08	107	used by the sender a use this as a receiving Receiver Identifier.	Mutually Defined Ther ID The published by the receiver of the data; What their sending ID, thus other parties sending ID to route data to them Value will contain the Standard Carrier tity of the service center if applicable. Materials is serviced by the service center of the service	ing to th Alpha C	em will

M	ISA09	I08	Interchange Dar Date of the intere		M	1	DT 6/6
			Date as YYMM	DD where:			
			YY	Year			
			MM	Month of Year			
			DD	Day			
M	ISA10	I09	Interchange Tin		M	1	TM 4/4
			Time of the inter	•			
			Time as HHMM	where:			
			HH	Hour			
			MM	Minute			
M	ISA11	165	element; this field of a simple data	icable; the repetition separator is a delimite ld provides the delimiter used to separate re- element or a composite data structure; this e data element separator, component elemen- ator	peated of value m t separat	t a da ccurr ust b or, a	rences e nd the
			U	U.S. EDI Community of ASC X12, T	DCC, an		
M	ISA12	I11	U	ontrol Version Number Code the version number of the interchange con Standards Approved for Publication by	ASCX	nents	ID 5/5
M	ISA13	I12	Interchange Co	Procedures Review Board through Oc	ober 20. M		N0 9/9
171	15A15	112		er assigned by the interchange sender	171	1	110 717
M	ISA14	I13		nt Requested Code	M	1	ID 1/1
-1-	-201-11		_	sender's request for an interchange acknowle No Interchange Acknowledgment Requ	dgment	_	22 2/2
M	ISA15	I14		age Indicator Code whether data enclosed by this interchange en	M		ID 1/1 t,
			P	Production Data			
			T	Test Data			
M	ISA16	I15	a data element; t data elements w	cable; the component element separator is a this field provides the delimiter used to separation a composite data structure; this value ment separator and the segment terminator	rate con	r and	ent

Segment: GS Functional Group Header

Position: 0075

Loop:

Level: Heading Usage: Mandatory

Max Use:

Purpose: Syntax Notes:

Semantic Notes:

To indicate the beginning of a functional group and to provide control information

- 1 GS04 is the group date.
- **2** GS05 is the group time.
- 3 The data interchange control number GS06 in this header must be identical to the same data element in the associated functional group trailer, GE02.

			Data Element Summar	y	
	Ref.	Data			
	Des.	Element	<u>Name</u>		<u>Attributes</u>
M	GS01	479	Functional Identifier Code	M	1 ID 2/2
			Code identifying a group of appli-	cation related transaction sets	
			Always 'SO'		
			SO Ocean Ship	ment Information	
M	GS02	142	Application Sender's Code	\mathbf{M}	1 AN 2/15
			Code identifying party sending tr	ansmission; codes agreed to by tra	nding
			partners		
			Customs Production		
			Customstst Testing		
M	GS03	124	Application Receiver's Code	M	1 AN 2/15
			Code identifying party receiving	transmission; codes agreed to by t	rading
			partners		
				ntain the Standard Carrier Alpha	
				vice center if applicable. May be	identical to
M	CCOA	272	the ISA08.	M	1 DT 0/0
M	GS04	373	Date Date expressed as CCVVMMDD	M O where CC represents the first two	1 DT 8/8
			the calendar year	where ee represents the first two	o digits of
			Date as CCYYMMDD where:		
			CC Century		
			YY Year		
			MM Month of Y	ear	
				Cai	
M	GS05	227	DD Day Time	M	1 TM 4/8
M	GSUS	337		time as follows: HHMM, or HH	
				where $H = hours (00-23)$, $M = m$	
				and DD = decimal seconds; decim	
			, ,	on this (0-9) and DD = hundredths ($^{\circ}$	
			Time as HHMM where:		
			HH Hour		
			MM Minute		
M	GS06	28	Group Control Number	M	1 N0 1/9
			Assigned number originated and	maintained by the sender	
M	GS07	455	Responsible Agency Code	M	1 ID 1/2
			Code identifying the issuer of the	standard; this code is used in con	junction
			with Data Element 480		
			Always 'X'		
			X Accredited	Standards Committee X12	
M	GS08	480	Version / Release / Industry Ide	entifier Code M	1 AN 1/12

Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed Always '006050'

006050

Standards Approved for Publication by ASC X12 Procedures Review Board through October 2012

Segment: ST Transaction Set Header

Position: 0100

Loop:

Level: Heading Usage: Mandatory

Max Use:

Purpose:

To indicate the start of a transaction set and to assign a control number

Syntax Notes: Semantic Notes:

- 1 The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).
- 2 The implementation convention reference (ST03) is used by the translation routines of the interchange partners to select the appropriate implementation convention to match the transaction set definition. When used, this implementation convention reference takes precedence over the implementation reference specified in the GS08.

	Ref. <u>Des.</u>	Data <u>Element</u>	<u>Name</u>		<u>A</u>	ttrib	<u>utes</u>
M	ST01	143		Set Identifier Code ring a Transaction Set	M	1	ID 3/3
			Always '355'				
			355	Customs Acceptance/Rejection			
M	ST02	329		Set Control Number	M	1	AN 4/9
				ontrol number that must be unique within the tra oup assigned by the originator for a transaction		ı set	
Not Used	ST03	1705	Implementa	tion Convention Reference	O	1	AN 1/35

Segment: M10 Manifest Identifying Information

Position: 0200

Loop:

Level: Heading Usage: Mandatory

Max Use:

Purpose:

To transmit manifest identifying information

Syntax Notes: 1 If either M1004 or M1010 is present, then the other is required.

2 If either M1015 or M1016 is present, then the other is required.

Semantic Notes:

- 1 M1004 is the International Maritime Organization (IMO) Vessel Code maintained in Lloyd's Register of Shipping.
- 2 M1007 is used for the six-digit Numeric Manifest Sequence Number.
- 3 M1011 indicates if the transmission involves an in-bond participant. A "Y" indicates it does; an "N" indicates it does not.
- 4 M1012 is a unique identification number for the manifest assigned by the originator of the manifest with a maximum length of 15.
- 5 M1017 is the type of initial manifest being amended by this transmission.

	Ref.	Data	Data	a Element Summary			
			Nama		A	44uih	utos
	<u>Des.</u> M1001	Element 140	Name Standard Co	arrier Alpha Code	$0^{\frac{\mathbf{A}}{\mathbf{A}}}$		outes ID 2/4
	MITOUT	140		-	O	1	11) 2/4
	M1002	91		ying the Standard Carrier Alpha Code ion Method/Type Code	0	1	ID 1/2
	W11002	71	-	V 1	_		11) 1/2
			Code specify:	ring the method or type of transportation for the sh	ıpment		
			О	Containerized Ocean			
			VE	Un-Containerized			
	M1003	26	Country Cod	de	O	1	ID 2/3
			Code identify	ying the country			
	M1004	597	Vessel Code		X	1	ID 1/8
			Code identify	ying the vessel			
	M1005	182	Vessel Name	•			
			Name of ship	as documented in "Lloyd's Register of Ships"			
Dep	M1006	55	Flight/Voyag	ge Number	0	1	AN 2/30
			Identifying d	esignator for the particular flight or voyage on wh	which the cargo		
			travels				
	M1007	127	Reference Id		O		AN 1/80
				formation as defined for a particular Transaction S	Set or as	8	
N T	3.51000	200		the Reference Identification Qualifier	•		D 4/4#
Not Used	M1008	380	Quantity		0		R 1/15
	M1009	256	Manifest Ty		O	1	ID 1/1
		_	•	ying the type of manifest transmitted			
		I	H	Arrival Notification from Carrier to U.S.			
				Used in response to 353 - Customs Even	ts Advi	sory	
		_		Details transaction set.			
		·	W	Original Manifest from Carrier to U.S. C			
				Used in response to the 309 - U.S. Custon	ns Mar	ifes	t
		,	Y	transaction set. Amendment to Manifest from Carrier to	HC C	4	
			I	Used in response to the 309 - U.S. Custon			
				transaction set.	1113 IVIAI	11103	ι
Not Used	M1010	897	Vessel Code		X	1	ID 1/1
				ring vessel code source			
	M1011	1073		dition or Response Code	O	1	ID 1/1
	M1012	127	Reference Id	dentification	O	1	AN 1/80

Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Not Used	M1013	353	Transaction Set Purpose Code	О	1 ID 2/2
Not Used	M1014	346	Application Type Code	O	1 ID 2/2
Not Used	M1015	580	Amendment Type Code	X	1 ID 1/1
Not Used	M1016	393	Amendment Code	X	1 ID 2/2
Not Used	M1017	256	Manifest Type Code	0	1 ID 1/1

Position: 0300

Loop:

Notes:

Level: Heading Usage: Optional Max Use: 10

Purpose:

Syntax Notes: Semantic Notes:

Notes:

To transmit information in a free-form format for comment or special instruction

The error message is returned in the K102.

	Ref. <u>Des.</u>	Data <u>Element</u>	Name	<u>A</u> 1	ttributes
M	K101	61	Free-form Information	M	1 AN 1/30
			Free-form information		
			This element will not be provided by CBP.		
	K102	61	Free-form Information	O	1 AN 1/30
			Free-form information		

Segment: P4 Port Information

Position: 0400

Loop: P4 Mandatory

Level: Heading Usage: Mandatory

Max Use:

Purpose: To transmit identifying information for a port

Syntax Notes:

Semantic Notes: 1 P401 is used for customs district and port code (census schedule D).

- 2 P402 is the estimated date of arrival.
- 3 P403 is used for number of bills of lading.
- 4 P404 is the Facilities Information and Resources Management System (FIRMS) Code.
- 5 P405 is the estimated time of arrival for P402.
- 6 P406 is the date conveyance departed prior port.
- 7 P407 is the time conveyance departed prior port.

	Ref.	Data				
	Des.	Element	<u>Name</u>	<u>At</u>	trib	<u>utes</u>
M	P401	310	Location Identifier	M	1	AN 1/30
			Code which identifies a specific location			
M	P402	373	Date	M	1	DT 8/8
			Date expressed as CCYYMMDD where CC represents the first	t two di	gits	of
			the calendar year			
Not Used	P403	380	Quantity	O	1	R 1/15
Required	P404	310	Location Identifier	O	1	AN 1/30
			Code which identifies a specific location			
	P405	337	Time	O	1	TM 4/8
			Time expressed in 24-hour clock time as follows: HHMM, or	HHMN	ASS	, or
			HHMMSSD, or HHMMSSDD, where $H = hours (00-23)$, M	= minu	tes (00-
			59), S = integer seconds (00-59) and DD = decimal seconds; d	ecimal s	seco	nds
			are expressed as follows: $D = tenths (0-9)$ and $DD = hundredt$	hs (00-9	99)	
Not Used	P406	373	Date	O	1	DT 8/8
Not Used	P407	337	Time	O	1	TM 4/8

Position: 0500

Loop: P4 Mandatory

Level: Heading Usage: Optional Max Use: 10

Purpose: To transmit information in a free-form format for comment or special instruction

Syntax Notes: Semantic Notes:

Notes: The error messages is returned in the K102

	Ref. <u>Des.</u>	Data Element	Name	Δ	ttributes
M	K101	61	Free-form Information	M	1 AN 1/30
			Free-form information		
			This element will not be provided by CBP.		
	K102	61	Free-form Information	О	1 AN 1/30
			Free-form information		

Segment: LX Transaction Set Line Number

Position: 0600

Loop: LX Optional

Level: Heading Usage: Optional

Max Use:

Purpose: To reference a line number in a transaction set

Syntax Notes: Semantic Notes:

Data Element Summary

Ref. Data
Des. Element Name

LX01 554 Assigned Number
Number assigned for differentiation within a transaction set

Attributes
M 1 N0 1/6

Segment: M13 Manifest Amendment Details

Position: 0700

Loop: M13 Optional

Level: Heading Usage: Optional Max Use: 1

Purpose: To correct a manifest record prior to conveyance arrival or to amend a manifest record

after conveyance arrival

Syntax Notes: 1 If either M1308 or M1310 is present, then the other is required.

2 If either M1311 or M1312 is present, then the other is required.

Semantic Notes: 1 M1301 is the bill of lading issuer code.

2 M1302 is used for discharge port (four-digit numeric census schedule D).

3 M1305 is new manifest quantity and is used if M1303 equals "R".

4 M1308 is used to report individual portions of a consolidated shipment.

5 M1309 is the conveyance operator's Standard Carrier Alpha Code (SCAC).

6 M1310 is the issuer code for the consolidated shipment.

Notes: Segment is returned if data found in error on original export message.

	Ref.	Data			
	Des.	Element	<u>Name</u>	Att	<u>ributes</u>
M	M1301	140	Standard Carrier Alpha Code	M	1 ID 2/4
			Code identifying the Standard Carrier Alpha Code		
M	M1302	310	Location Identifier	M	1 AN 1/30
			Code which identifies a specific location		
	M1303	580	Amendment Type Code	O	1 ID 1/1
			Code identifying type of manifest amendment		
M	M1304	598	Bill of Lading/Waybill Number	M	1 AN 1/50
			Identification number assigned to the shipment by the carrier of	r consoli	dator
	M1305	380	Quantity	O	1 R 1/15
			Numeric value of quantity		
	M1306	393	Amendment Code	O	1 ID 2/2
			Code specifying the reasons for the amendment of the manifest	record	
	M1307	306	Action Code	O	1 ID ½
			Code indicating type of action		
	M1308	598	Bill of Lading/Waybill Number	X	1 AN 1/50
			Identification number assigned to the shipment by carrier or		
			consolidator	O	1 ID 2/4
	M1309	140	Standard Carrier Alpha Code		
			Code identifying the Standard Carrier Alpha Code		
Not Used	M1310	140	Standard Carrier Alpha Code	X	1 ID 2/4
Not Used	M1311	66	Identification Code Qualifier	X	1 ID 1/2
Not Used	M1312	67	Identification Code	X	1 AN 2/80

Position: 0800

Loop: M13 Optional

Level: Heading Usage: Optional Max Use: 10

Purpose: To transmit information in a free-form format for comment or special instruction

Syntax Notes: Semantic Notes:

Notes: The error message is returned in the K102.

	Ref. <u>Des.</u>	Data <u>Element</u>	Name	<u>A</u>	ttributes
M	K101	61	Free-form Information	\mathbf{M}	1 AN 1/30
			Free-form information		
			This element will not be provided by CBP.		
	K102	61	Free-form Information	O	1 AN 1/30
			Free-form information		

M11 Manifest Bill of Lading Details **Segment:**

Position: 0900

> M11 Loop: Optional

Level: Heading Optional Usage: Max Use: 1

To transmit bill of lading detail information for a manifest **Purpose:**

If either M1103 or M1104 is present, then the other is required. **Syntax Notes:**

- If either M1105 or M1106 is present, then the other is required.
- 3 If either M1107 or M1108 is present, then the other is required.
- 4 If either M1111 or M1113 is present, then the other is required.
- 5 If M1115 is present, then M1114 is required.
- 6 If M1118 is present, then M1115 is required.
- 7 If M1119 is present, then M1118 is required.

Semantic Notes:

- 1 M1101 is the unique bill of lading number.
- M1102 is used for foreign port where the cargo is loaded.
- 3 M1103 is used for total number of pieces on a bill of lading using the smallest package unit (maximum eight-digits).
- 4 M1104 is the smallest package unit code.
- M1111 is the house bill number for consolidation.
- M1112 is the unique bill of lading issuer code.
- M1113 is the issuer code of the consolidated shipment.
- M1114 is the code of the secondary party nominated to receive bill of lading status notifications.
- M1115 is the code of the second secondary party nominated to receive bill of lading status notifications.
- 10 M1118 is the Standard Carrier Alpha Code (SCAC) of an additional second notify
- 11 M1119 is the Standard Carrier Alpha Code (SCAC) of an additional second notify carrier.
- 12 M1120 is the last place/port prior to loading.
- 13 M1121 is the first foreign port where the carrier takes possession of the cargo.
- 14 M1122 identifies mode of transportation from the last place/port prior to loading.
- 15 M1123 is the method of payment for transportation.
- 16 M1124 is the Maritime Administration Cargo Preference Program Code (see code source 926).
- 17 M1125 identifies the reporting identifier used for Port of Lading in M1102.
- 18 M1127 is the date the Goods returning to the U.S., Canada or Mexico departed the U.S., Canada, or Mexico.
- 19 M1128 is the indicator as to whether the Goods returning to the U.S., Canada or Mexico never left the control of the foreign country's Customs or the border crossing carrier while out of the country. A "Y" indicates the Goods never left the control of Customs or the border crossing carrier while out of the country. An "N" indicates the Goods did leave the control of foreign country's Customs or the border crossing carrier while out of the country.

Segment is returned if data found in error on inbound message. **Notes:**

Data

	Reī.	Data			
	Des.	Element	<u>Name</u>	Att	<u>tributes</u>
M	M1101	598	Bill of Lading/Waybill Number	M	1 AN 1/50
			Identification number assigned to the shipment by the carrier or	consoli	dator
M	M1102	310	Location Identifier	M	1 AN 1/30
			Code which identifies a specific location		
Must Use	M1103	380	Quantity	X	1 R 1/15
			Numeric value of quantity		
Must Use	M1104	599	Manifest Unit Code	\mathbf{X}	1 ID 1/3
			Code specifying the smallest package unit for the bill of lading		
Must Use	M1105	81	Weight	\mathbf{X}	1 R 1/10

			Numeric value of weight			
Must Use	M1106	188	Weight Unit Code	X	1	ID 1/1
			Code specifying the weight unit			
	M1107	183	Volume	X	1	R 1/8
	M1108	184	Volume Unit Qualifier	X	1	ID 1/1
	M1109	582	Bill of Lading Type Code	0	1	ID 2/2
			Code identifying the type of bill of lading			
	M1110	600	Place of Receipt by Pre-carrier	0	1	AN 1/17
			The city or country in which the pre-carrier took possess	ion of the car	go	
Not Used	M1111	598	Bill of Lading/Waybill Number	X	1	AN 1/50
M	M1112	140	Standard Carrier Alpha Code	M	1	ID 2/4
			Code identifying the Standard Carrier Alpha Code			
Not Used	M1113	140	Standard Carrier Alpha Code	X	1	ID 2/4
	M1114	140	Standard Carrier Alpha Code	X	1	ID 2/4
			Code identifying the Standard Carrier Alpha Code			
	M1115	140	Standard Carrier Alpha Code	X	1	ID 2/4
			Code identifying the Standard Carrier Alpha Code			
Not Used	M1116	1302	Shipper's Export Declaration Requirements	O	1	AN 1/2
Not Used	M1117	1578	Export Exception Code	O	1	ID 2/2
Not Used	M1118	140	Standard Carrier Alpha Code	X		ID 2/4
Not Used	M1119	140	Standard Carrier Alpha Code	O	1	ID 2/4
	M1120	310	Location Identifier	O	1	AN 1/30
	M1121	310	Location Identifier	0	1	AN 1/30
	M1122	91	Transportation Method/Type Code	O	1	ID 1/2
	M1123	591	Payment Method Code	O	1	ID 3/3
Not Used	M1124	1271	Industry Code	O	1	AN 1/30
Not Used	M1125	309	Location Qualifier	M		ID 1/2
Not Used	M1126	284	Service Level Code	O		ID 2/2
Not Used	M1127	373	Date	O		DT 8/8
Not Used	M1128	1073	Yes/No Condition or Response Code	0	1	ID 1/1

Position: 1000

Loop: M11 Optional

Level: Heading Usage: Optional Max Use: 10

Purpose: To transmit information in a free-form format for comment or special instruction

Syntax Notes: Semantic Notes:

Notes: The error message is returned in the K102.

	Ref. <u>Des.</u>	Data <u>Element</u>	Name	<u>A</u>	ttributes
M	K101	61	Free-form Information	M	1 AN 1/30
			Free-form information		
			This element will not be provided by CBP.		
	K102	61	Free-form Information	O	1 AN 1/30
			Free-form information		

Segment: N9 Extended Reference Information

Position: 1050

Loop: N9 Optional

Level: Heading Usage: Optional Max Use: 1

Purpose: To transmit identifying information as specified by the Reference Identification Qualifier

Syntax Notes: 1 At least one of N902 or N903 is required.
2 If N906 is present, then N905 is required.

If N906 is present, then N905 is required.If either C04003 or C04004 is present, then the other is required.

4 If either C04005 or C04006 is present, then the other is required.

Semantic Notes: 1 N906 reflects the time zone which the time reflects.

2 N907 contains data relating to the value cited in N902.

Notes: Segment is returned if data found in error on inbound message.

	Ref.	Data	·			
	Des.	Element	<u>Name</u>	<u>A</u>	<u>ttril</u>	<u>outes</u>
M	N901	128	Reference Identification Qualifier Code identifying the Reference Identification	M	1	ID 2/3
	N902	127	Reference Identification	X	1	AN 1/80
			Reference information as defined for a particular Transaction specified by the Reference Identification Qualifier	on Set or a	S	
Not Used	N903	369	Free-form Description	X	1	AN 1/45
Not Used	N904	373	Date	O	1	DT 8/8
Not Used	N905	337	Time	X	1	TM 4/8
Not Used	N906	623	Time Code	O	1	ID 2/2
Not Used	N907	C040	Reference Identifier	O	1	
Not Used	C04001	128	Reference Identification Qualifier	M	1	ID 2/3
Not Used	C04002	127	Reference Identification	M	1	AN 1/80
Not Used	C04003	128	Reference Identification Qualifier	X	1	ID 2/3
Not Used	C04004	127	Reference Identification	X	1	AN 1/80
Not Used	C04005	128	Reference Identification Qualifier	X	1	ID 2/3
Not Used	C04006	127	Reference Identification	X	1	AN 1/80

Position: 1070

Loop: N9 Optional

Level: Heading Usage: Optional Max Use: 10

Purpose: To transmit information in a free-form format for comment or special instruction

Syntax Notes: Semantic Notes:

Notes: The error message is returned in the K102.

	Ref. <u>Des.</u>	Data <u>Element</u>	Name	<u>A</u>	ttributes_
M	K101	61	Free-form Information	M	1 AN 1/30
			Free-form information		
			This element will not be provided by CBP.		
	K102	61	Free-form Information	O	1 AN 1/30
			Free-form information		

Segment: N1 Party Identification

Position: 1100

Loop: N1 Optional

Level: Heading Usage: Optional Max Use: 1

Purpose: To identify a party by type of organization, name, and code

Syntax Notes: 1 At least one of N102 or N103 is required.

2 If either N103 or N104 is present, then the other is required.

Semantic Notes:

Notes: Segment is returned if data found in error on inbound message.

	Ref.	Data	·		
	Des.	Element	<u>Name</u>	<u>A</u>	<u>ttributes</u>
M	N101	98	Entity Identifier Code	M	1 ID 2/3
			Code identifying an organizational entity, a physical location, individual	property	y or an
	N102	93	Name	\mathbf{X}	1 AN 1/60
			Free-form name		
	N103	66	Identification Code Qualifier	\mathbf{X}	1 ID 1/2
			Code specifying the system/method of code structure used for Code (67)	Identifi	cation
	N104	67	Identification Code	\mathbf{X}	1 AN 2/80
			Code identifying a party or other code		
Not Used	N105	706	Entity Relationship Code	O	1 ID 2/2
Not Used	N106	98	Entity Identifier Code	O	1 ID 2/3

Position: 1200

Loop: N1 Optional

Level: Heading Usage: Optional Max Use: 10

Purpose: To transmit information in a free-form format for comment or special instruction

Syntax Notes: Semantic Notes:

Notes: The error message is returned in the K102.

	Ref. <u>Des.</u>	Data <u>Element</u>	Name	<u>A</u>	ttributes
M	K101	61	Free-form Information	M	1 AN 1/30
			Free-form information		
			This element will not be provided by CBP.		
	K102	61	Free-form Information	O	1 AN 1/30
			Free-form information		

N3 Party Location **Segment:**

1300 **Position:**

Loop: N3 Optional

Level: Heading Optional Usage: Max Use:

To specify the location of the named party **Purpose:**

Syntax Notes: Semantic Notes:

> Segment is returned if data found in error on inbound message. **Notes:**

	Ref.	Data	Data Diement Sammary		
	Des.	Element	<u>Name</u>	<u>A</u> 1	<u>ttributes</u>
M	N301	166	Address Information Address information	M	1 AN 1/55
	N302	166	Address Information Address information	0	1 AN 1/55

Position: 1400

Loop: N3 Optional

Level: Heading Usage: Optional Max Use: 10

Purpose: To transmit information in a free-form format for comment or special instruction

Syntax Notes: Semantic Notes:

Notes: The error message is returned in the K102.

	Ref. <u>Des.</u>	Data <u>Element</u>	Name	<u>A</u>	ttributes
M	K101	61	Free-form Information	M	1 AN 1/30
			Free-form information		
			This element will not be provided by CBP.		
	K102	61	Free-form Information	O	1 AN 1/30
			Free-form information		

Segment: N4 Geographic Location

Position: 1410

Loop: N4 Optional

Level: Heading Usage: Optional Max Use: 1

Purpose: To specify the geographic place of the named party
Syntax Notes: 1 Only one of N402 or N407 may be present.

Only one of N403 or N408 may be present.
If N406 is present, then N405 is required.

4 If N407 is present, then N404 is required.

Semantic Notes:

Notes: Segment is returned if data found in error on inbound message.

	Ref.	Data				
	Des.	Element	<u>Name</u>	<u>A</u>	ttrib	<u>utes</u>
	N401	19	City Name	O	1	AN 2/30
	N402	156	Free-form text for city name State or Province Code Code specifying the Standard State/Province as defined by app	X propriat	1 e	ID 2/2
	N403	116	government agency Postal Code Code considerational model constant and constant an	X		ID 3/15
	N404	26	Code specifying international postal zone code excluding pun blanks (zip code for United States) Country Code	X		ID 2/3
Not Used Not Used	N405 N406	309 310	Code identifying the country Location Qualifier Location Identifier	X O		ID 1/2 AN 1/30
Not Used Not Used	N407 N408	1715 1702	Country Subdivision Code Postal Code-Formatted	X X	1	ID 1/3 AN 3/20

Position: 1420

Loop: N4 Optional

Level: Heading Usage: Optional Max Use: 10

Purpose: To transmit information in a free-form format for comment or special instruction

Syntax Notes: Semantic Notes:

Notes: The error message is returned in the K102.

	Ref. <u>Des.</u>	Data <u>Element</u>	Name	<u>A</u>	ttributes
M	K101	61	Free-form Information	M	1 AN 1/30
			Free-form information		
			This element will not be provided by CBP.		
	K102	61	Free-form Information	O	1 AN 1/30
			Free-form information		

Segment: PER Administrative Communications Contact

Position: 1440

Loop: PER Optional

Level: Heading Usage: Optional Max Use: 1

Purpose: To identify a person or office to whom administrative communications should be directed

Syntax Notes:

If either PER03 or PER04 is present, then the other is required.
 If either PER05 or PER06 is present, then the other is required.

3 If either PER05 or PER06 is present, then the other is required.

Semantic Notes:

Notes: Segment is returned if data found in error on inbound message.

	Ref.	Data			
	Des.	Element	<u>Name</u>	<u>A</u>	<u>ttributes</u>
M	PER01	366	Contact Function Code	M	1 ID 2/2
			Code identifying the major duty or responsibility of the p erso	on or gro	up named
	PER02	93	Name	O	1 AN 1/60
			Free-form name		
	PER03	365	Communication Number Qualifier	X	1 ID 2/2
			Code identifying the type of communication number		
	PER04	364	Communication Number	X	1 AN 1/256
			Complete communications number including country or area applicable	a code wł	nen
Not Used	PER05	365	Communication Number Qualifier	\mathbf{X}	1 ID 2/2
Not Used	PER06	364	Communication Number	\mathbf{X}	1 AN 1/256
Not Used	PER07	365	Communication Number Qualifier	X	1 ID 2/2
Not Used	PER08	364	Communication Number	X	1 AN 1/256
Not Used	PER09	443	Contact Inquiry Reference	O	1 AN 1/20

Position: 1450

Loop: PER Optional

Level: Heading Usage: Optional Max Use: 10

Purpose: To transmit information in a free-form format for comment or special instruction

Syntax Notes: Semantic Notes:

Notes: The error message is returned in the K102.

	Ref. <u>Des.</u>	Data <u>Element</u>	Name	<u>A</u>	ttributes
M	K101	61	Free-form Information	\mathbf{M}	1 AN 1/30
			Free-form information		
			This element will not be provided by CBP.		
	K102	61	Free-form Information	O	1 AN 1/30
			Free-form information		

Segment: M15 Customs Events Advisory Details

Position: 1630

Loop: M15 Optional

Level: Heading Usage: Optional Max Use: 1

Purpose: To notify Customs of in-bond cargo movement or of a conveyance arrival or departure,

or of transfer of custodial liability when an in-bond movement involves multiple legs

Syntax Notes: 1 At least one of M1504 or M1510 is required.

- 2 If M1511 is present, then M1510 is required.
- 3 If either M1513 or M1514 is present, then the other is required.
- 4 If M1515 is present, then M1516 is required.
- 5 If either M1518 or M1519 is present, then the other is required.

Semantic Notes: 1 M1503 is the start date of the event.

- 2 M1504 is the Schedule D code for place of cargo movement, transfer of liability or conveyance arrival or departure.
- 3 M1505 is the unique bill of lading issuer code, required when M1501 is "2", "6", or "B".
- 4 M1506 is the start time of the event.
- 5 M1508 is the Internal Revenue Service identification number of the next in-bond carrier.
- 6 M1509 is the Standard Carrier Alpha Code (SCAC) of the next in-bond carrier.
- 7 M1510 is the city in which a transfer of custodial liability occurs.
- 8 M1511 is the state or province code for the city named in M1510.
- 9 If M1512 is "Y", then M1504 is an intermediate port. If "N", then M1504 is the port of final destination.
- 10 M1515 is the name of the exporting vessel.
- 11 M1517 is the last foreign port prior to sailing for the United States.
- 12 M1518 is the end date of the event.
- 13 M1519 is the end time of the event.

Notes: Segment is returned if data found in error on inbound message.

	Ref.	Data				
	Des.	Element	<u>Name</u>	<u>At</u>	tribu	<u>tes</u>
M	M1501	1497	Notification Entity Qualifier	M	1 A	AN 1/2
			Code indicating type of notifications			
M	M1502	127	Reference Identification	\mathbf{M}	1 A	AN 1/80
			Reference information as defined for a particular Transaction S specified by the Reference Identification Qualifier	et or as		
M	M1503	373	Date	M	1 I	OT 8/8
			Date expressed as CCYYMMDD where CC represents the first the calendar year	two di	gits of	f
	M1504	310	Location Identifier	X	1	AN 1/30
	W11304	310		A	1 /	A11 1/50
			Code which identifies a specific location			
Not used	M1505	140	Standard Carrier Alpha Code	O	1]	ID 2/4
			Code identifying the Standard Carrier Alpha Code			
M	M1506	337	Time	M	1 7	TM 4/8
			Time expressed in 24-hour clock time as follows: HHMM, or	HHMN	MSS,	or
			HHMMSSD, or HHMMSSDD, where $H = hours (00-23)$, M	= minu	tes (0	0-
			59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds	ecimal s	secon	ds
			are expressed as follows: $D = tenths (0-9)$ and $DD = hundredt$	hs (00-9	99)	
Not Used	M1507	225	Seal Number	Ò	1	AN 2/15
Not Used	M1508	127	Reference Identification	O	1 4	AN 1/80
Not Used	M1509	140	Standard Carrier Alpha Code	O	1 l	ID 2/4
Not Used	M1510	19	City Name	\mathbf{X}	1 /	AN 2/30
Not Used	M1511	156	State or Province Code	O	1 l	ID 2/2
Not Used	M1512	1073	Yes/No Condition or Response Code	O	1 l	ID 1/1
Not Used	M1513	128	Reference Identification Qualifier	X	1 l	ID 2/3

Not Used	M1514	127	Reference Identification	X	1 AN 1/80
Not Used	M1515	182	Vessel Name	0	1 AN 2/28
Not Used	M1516	91	Transportation Method/Type Code	X	1 ID 1/2
	M1517	310	Location Identifier	0	1 AN 1/30
Not Used	M1518	373	Date	X	1 DT 8/8
Not Used	M1519	337	Time	X	1 TM 4/8

Position: 1640

Loop: M15 Optional

Level: Heading Usage: Optional Max Use: 10

Purpose: To transmit information in a free-form format for comment or special instruction

Syntax Notes: Semantic Notes:

Notes: The error message is returned in the K102.

	Ref. <u>Des.</u>	Data <u>Element</u>	Name	<u>A</u>	ttributes
M	K101	61	Free-form Information	M	1 AN 1/30
			Free-form information		
			This element will not be provided by CBP.		
	K102	61	Free-form Information	O	1 AN 1/30
			Free-form information		

Segment: VID Conveyance Identification

Position: 1700

Loop: VID Optional

Level: Heading Usage: Optional Max Use: 1

Purpose: To identify a conveyance and its attributes

Syntax Notes: 1 If VID14 is present, then at least one of VID15 or VID18 is required.

Only one of VID15 or VID18 may be present.
If VID15 is present, then VID16 is required.

4 If VID16 is present, then at least one of VID15 or VID18 is required.

5 If VID18 is present, then VID16 is required.

Semantic Notes: 1 VID12 is the Census Schedule K code for the foreign port of loading on a vessel.

2 VID13 is the Standard Carrier Alpha Code (SCAC) of the Haulage Rights Carrier.

3 VID14 is the license plate of the equipment.

VID15 is the state or province of the license in the VID14.
VID16 is the country of the license in the VID15 or VID18.

6 VID17 is the ACE (Automated Commercial Environment) ID of the equipment identified in the VID03.

7 VID18 is the country subdivision of the license in the VID14.

Notes: Segment is returned if data found in error on inbound message.

	Ref.	Data	2 2.0			
	Des.	Element	Name	\mathbf{A}^{1}	ttrib	utes
M	VID01	40	Equipment Description Code	M	1	ID 2/2
			Code identifying type of equipment used for shipment			
	VID02	206	Equipment Initial	0	1	AN 1/4
			Prefix or alphabetic part of an equipment unit's identifying nur	nber		
M	VID03	207	Equipment Number	M	1	AN 1/15
			Sequencing or serial part of an equipment unit's identifying nu numeric form for equipment number is preferred)	mber (p	oure	
	VID04	225	Seal Number	O	1	AN 2/15
			Unique number on seal used to close a shipment			
	VID05	225	Seal Number	O	1	AN 2/15
			Unique number on seal used to close a shipment			
Not Used	VID06	567	Equipment Length	O	1	N0 4/5
Not Used	VID07	65	Height	O	1	R 1/8
Not Used	VID08	189	Width	O	1	R 1/8
Not Used	VID09	24	Equipment Type Code	O	1	ID 4/4
	VID10	322	Load/Empty Status Code	O	1	ID 1/1
			Code specifying the loaded condition of transportation equipm	ent		
Not Used	VID11	56	Type of Service Code	O	1	ID 2/2
Not Used	VID12	310	Location Identifier	O	1	AN 1/30
Not Used	VID13	140	Standard Carrier Alpha Code	O	1	ID 2/4
Not Used	VID14	127	Reference Identification	O	1	AN 1/80
Not Used	VID15	156	State or Province Code	\mathbf{X}	1	ID 2/2
Not Used	VID16	26	Country Code	\mathbf{X}	1	ID 2/3
Not Used	VID17	127	Reference Identification	O	1	AN 1/80
Not Used	VID18	1715	Country Subdivision Code	\mathbf{X}		ID 1/3
Not Used	VID19	512	Import/Export Code	O	_	ID 1/1
Not Used	VID20	761	Equipment Number Check Digit	O	1	N0 1/1

Position: 1701

Loop: VID Optional

Level: Heading Usage: Optional Max Use: 10

Purpose: To transmit information in a free-form format for comment or special instruction

Syntax Notes: Semantic Notes:

Notes: The error message is returned in the K102.

	Ref. <u>Des.</u>	Data <u>Element</u>	Name	<u>A</u>	ttributes
M	K101	61	Free-form Information	M	1 AN 1/30
			Free-form information		
			This element will not be provided by CBP.		
	K102	61	Free-form Information	O	1 AN 1/30
			Free-form information		

Segment: M7 Seal Numbers

Position: 1720

Loop: M7 Optional

Level: Heading Usage: Optional Max Use: 1

Purpose: To record seal numbers used and the organization that applied the seals

Syntax Notes: Semantic Notes:

	Ref.	Data			
	Des.	Element	<u>Name</u>	<u>A</u> :	<u>ttributes</u>
M	M701	225	Seal Number	M	1 AN 2/15
			Unique number on seal used to close a shipment		
	M702	225	Seal Number	O	1 AN 2/15
			Unique number on seal used to close a shipment		
	M703	225	Seal Number	O	1 AN 2/15
			Unique number on seal used to close a shipment		
	M704	225	Seal Number	O	1 AN 2/15
			Unique number on seal used to close a shipment		
Not Used	M705	98	Entity Identifier Code	O	1 ID 2/3

Position: 1721

Loop: M7 Optional

Level: Heading Usage: Optional Max Use: 10

Purpose: To transmit information in a free-form format for comment or special instruction

Syntax Notes: Semantic Notes:

Notes: The error message is returned in the K102.

	Ref. <u>Des.</u>	Data <u>Element</u>	Name	<u>A</u>	ttributes
M	K101	61	Free-form Information	M	1 AN 1/30
			Free-form information		
			This element will not be provided by CBP.		
	K102	61	Free-form Information	O	1 AN 1/30
			Free-form information		

Segment: M7A Seal Number Replacement

Position: 1741

Loop: M7A Optional

Level: Heading Usage: Optional Max Use: 1

Purpose: To provide an audit trail of seal number changes

Syntax Notes: 1 If either M7A04 or M7A05 is present, then the other is required.

Semantic Notes: 1 M7A01 is the original seal number.

2 M7A02 is the replacement seal number.

M7A03 is the date the new seal was installed.

4 M7A04 and M7A05 indicate the party responsible for the seal replacement.

5 M7A06 is a description of why the seal was replaced.

6 M7A07 is the location of the replaced seal on the equipment.

Data Element Summary

Ref.	Data					
Des.	Element	<u>Name</u>	<u>A</u> 1	<u>ttributes</u>		
M7A01	225	Seal Number	M	1 AN 2/15		
		Unique number on seal used to close a shipment				
M7A02	225	Seal Number	M	1 AN 2/15		
		Unique number on seal used to close a shipment				
M7A03	373	Date	O	1 DT 8/8		
			t two di	igits of		
M7A4	98		X	1 ID 2/3		
M7A5	93	Name	\mathbf{X}	1 AN 1/60		
		Free form name				
M7A6	352	Description	O			
		A free-form description to clarify the related data elements and their content				
M7A07	302	Location on Equipment Code	O			
	Des. M7A01 M7A02 M7A03 M7A4 M7A5 M7A6	Des. M7A01 Element 225 M7A02 225 M7A03 373 M7A4 98 M7A5 93 M7A6 352	Des. M7A01Element 225Name Seal Number Unique number on seal used to close a shipmentM7A02225Seal Number Unique number on seal used to close a shipmentM7A03373DateDate expressed as CCYYMMDD where CC represents the first the calendar yearM7A498Entity Identifier Code Code identifying an organizational entity, physical property, orM7A593Name Free form nameM7A6352Description A free-form description to clarify the related data elements and their content	Des. Element M7A01 Name Seal Number Additional Management M7A02 225 Seal Number Unique number on seal used to close a shipment M M7A03 373 Date O Date expressed as CCYYMMDD where CC represents the first two distance the calendar year X M7A4 98 Entity Identifier Code Code identifying an organizational entity, physical property, or an indistance of the composition of t		

Code indicating a location on a piece of equipment, as observed from the rearend. The rear-end of the equipment is based on the equipment type (i.e. container door, chassis wheels, brakes.)

Position: 1751

Loop: M7A Optional

Level: Heading Usage: Optional Max Use: 1

Purpose: To transmit information in a free-form format for comment or special instruction

Syntax Notes: Semantic Notes:

Notes: The error message is returned in the K102.

	Ref. <u>Des.</u>	Data <u>Element</u>	Name	<u>A</u>	ttributes
M	K101	61	Free-form Information	M	1 AN 1/30
			Free-form information		
			This element will not be provided by CBP.		
	K102	61	Free-form Information	O	1 AN 1/30
			Free-form information		

Segment: VC Motor Vehicle Control

Position: 2000

Loop: VC Optional

Level: Heading Usage: Optional Max Use: 1

Purpose: To define motor vehicle identification and logistics

Syntax Notes:

Semantic Notes: 1 VC05 is the automotive manufacturer route code.

2 VC12 is the direction the headlights of the vehicle point.

3 VC13 is the final destination ramp location as assigned by the manufacturer.

Notes: Segment is returned if data found in error on inbound message.

	Ref.	Data			
	Des.	Element	<u>Name</u>	<u>A</u>	<u>ttributes</u>
M	VC01	539	Vehicle Identification Number	\mathbf{M}	1 AN 1/30
			Unique identification number stamped on the vehicle by the	manufact	urer
Not Used	VC02	836	Vehicle Deck Position Code	O	1 ID 2/2
Not Used	VC03	837	Vehicle Type Code	O	1 ID 1/1
Not Used	VC04	838	Dealer Code	O	1 AN 2/9
Not Used	VC05	1	Route Code	O	1 AN 1/13
Not Used	VC06	839	Bay Location	O	1 AN 1/6
Not Used	VC07	833	Automotive Manufacturers Code	O	1 ID 2/2
Not Used	VC08	308	Damage Exception Indicator Code	O	1 ID 1/1
Not Used	VC09	835	Supplemental Inspection Code	O	1 ID 1/1
	VC10	583	Factory Car Order Number	O	1 AN 6/10
			This number to be supplied by the shipper for Canadian customer requirements at border points for all finished motor vehicles exported to the United States from Canada		
Not Used	VC11	877	Vessel Stowage Location	O	1 AN 1/12
Not Used	VC12	1543	Equipment Orientation Code	O	1 ID 1/1
Not Used	VC13	310	Location Identifier	O	1 AN 1/30

Position: 2050

Loop: VC Optional Level: Heading

Level: Heading Usage: Optional Max Use: 10

Purpose: To transmit information in a free-form format for comment or special instruction

Syntax Notes: Semantic Notes:

Notes: The error message is returned in the K102.

	Ref. <u>Des.</u>	Data <u>Element</u>	Name	<u>A</u>	ttributes
M	K101	61	Free-form Information	M	1 AN 1/30
			Free-form information		
			This element will not be provided by CBP.		
	K102	61	Free-form Information	O	1 AN 1/30
			Free-form information		

N10 Quantity and Description **Segment:**

Position: 2100

> N10 Loop: Optional

Level: Heading Usage: Optional Max Use: 1

Purpose: To indicate line item quantity, description, marks and numbers, commodity code, weight,

and customs value

Syntax Notes: If either N1004 or N1005 is present, then the other is required.

> If either N1007 or N1008 is present, then the other is required. 2

If N1013 is present, then N1006 is required. 3

Semantic Notes: 1 If N1013 is not used, the default currency of N1006 is USD (US Dollar).

> 2 N1009 is the U.S. Customs and Border Protection (CBP) bar code number for line

release.

3 N1011 is the country of the manufacturer of the goods.

N1012 is the country of the final destination of the goods.

N1013 is the currency of the value of N1006.

Notes: Segment is returned if data found in error on inbound message.

Ref. Des.	Data <u>Element</u>	Name	Att	rib	utes_
N1001	380	Quantity	0	1	R 1/15
		Numeric value of quantity			
N1002	369	Free-form Description	O	1	AN 1/45
		Free-form descriptive text			
N1003	87	Marks and Numbers	O	1	AN 1/48
		Marks and numbers used to identify a shipment or parts of a ship	ipment		
N1004	23	Commodity Code Qualifier	X	1	ID 1/1
		Code identifying the commodity coding system used for Comm	odity C	ode	
N1005	22	Commodity Code	X	1	AN 1/30
		Code describing a commodity or group of commodities			
N1006	602	Customs Shipment Value	X	1	AN 2/8
		Customs value in whole dollars			
N1007	188	Weight Unit Code	\mathbf{X}	1	ID 1/1
		Code specifying the weight unit			
N1008	81	Weight	X	1	R 1/10
		Numeric value of weight			
N1009	127	Reference Identification	O	1	AN 1/80
		Reference information as defined for a particular Transaction S	et or as		
		specified by the Reference Identification Qualifier			
N1010	599	Manifest Unit Code	0	1	ID 1/3
		Code specifying the smallest package unit for the bill of lading			
N1011	26	Country Code	O	1	ID 2/3
		Code identifying the country			
Not Used N1012	26	Country Code	0		ID 2/3
Not Used N1013	100	Currency Code	O	1	ID 3/3

Position: 2150

Loop: N10 Optional

Level: Heading Usage: Optional Max Use: 10

Purpose: To transmit information in a free-form format for comment or special instruction

Syntax Notes: Semantic Notes:

Notes: The error message is returned in the K102.

	Ref. <u>Des.</u>	Data <u>Element</u>	Name	<u>A</u>	ttributes
M	K101	61	Free-form Information	\mathbf{M}	1 AN 1/30
			Free-form information		
			This element will not be provided by CBP.		
	K102	61	Free-form Information	O	1 AN 1/30
			Free-form information		

Segment: H1 Hazardous Material

Position: 2200

Loop: H1 Optional

Level: Heading Usage: Optional Max Use: 1

Purpose: To specify information relative to hazardous material

Syntax Notes: 1 If either H107 or H108 is present, then the other is required.

Semantic Notes:

	Ref.	Data			
	Des.	Element	<u>Name</u>	<u>A</u>	<u>ttributes</u>
M	H101	62	Hazardous Material Code	\mathbf{M}	1 AN 4/10
			Code relating to hazardous material code qualifier for regulate materials	d hazar	dous
	H102	209	Hazardous Material Class Code	O	1 AN 1/4
			Code specifying the kind of hazard for the material		
	H103	208	Hazardous Material Code Qualifier	O	1 ID 1/1
			Code which qualifies the Hazardous Material class code		
	H104	64	Hazardous Material Description	O	1 AN 2/30
			Material name, special instructions, and phone number if any		
	H105	63	Hazardous Material Contact	O	1 AN 1/24
			Phone number and name of person or department to contact in emergency	case of	f
	H106	200	Hazardous Materials Page	\mathbf{O}	1 AN 1/6
			The United Nations page number as required for the international transport of hazardous materials		
	H107	77	Flashpoint Temperature	\mathbf{X}	1 N 1/3
	H108	355	Unit or Basis for Measurement Code	X	1 ID 2/2
			Code specifying the units in which a value is being expressed, which a measurement has been taken	or man	ner in
Not Used	H109	254	Packing Group Code	O	1 ID 1/3

Position: 2300

Loop: H1 Optional

Level: Heading Usage: Optional Max Use: 10

Purpose: To transmit information in a free-form format for comment or special instruction

Syntax Notes: Semantic Notes:

Notes: The error message is returned in the K102.

	Ref. <u>Des.</u>	Data <u>Element</u>	Name	<u>A</u>	ttributes
M	K101	61	Free-form Information	\mathbf{M}	1 AN 1/30
			Free-form information		
			This element will not be provided by CBP.		
	K102	61	Free-form Information	O	1 AN 1/30
			Free-form information		

Segment: **H2** Additional Hazardous Material Description

Position: 2400

Loop: H2 Optional

Level: Heading Usage: Optional Max Use: 1

Purpose: To specify free-form hazardous material descriptive data in addition to the information

provided in the H1 segment

Syntax Notes: Semantic Notes:

Notes: Segment is returned if data found in error on inbound message.

	Ref.	Data			
	Des.	Element	<u>Name</u>		Attributes
M	H201	64	Hazardous Material Description	M	1 AN 2/30
			Material name, special instructions, and phone number if any		
Not Used	H202	274	Hazardous Material Classification	O	1 AN 1/30

Position: 2500

Loop: H2 Optional

Level: Heading Usage: Optional Max Use: 10

Purpose: To transmit information in a free-form format for comment or special instruction

Syntax Notes: Semantic Notes:

Notes: The error message is returned in the K102.

	Ref. <u>Des.</u>	Data <u>Element</u>	Name	<u>A</u>	ttributes
M	K101	61	Free-form Information	\mathbf{M}	1 AN 1/30
			Free-form information		
			This element will not be provided by CBP.		
	K102	61	Free-form Information	O	1 AN 1/30
			Free-form information		

Segment: K3 File Information

Position: 0100

Loop:

Level: Detail
Usage: Mandatory

Max Use:

Purpose:

To transmit a fixed-format record or matrix contents

Syntax Notes:

Semantic Notes:

1 K303 identifies the value of the index.

Used to summarize and report the cumulative results of a transmission to AMS.

Notes: Used to summarize and re-

Used to summarize and re	Used to summarize and report the cumulative results of a transmission to AMS.							
Data Element Le	ngth/Class	s Description						
Carrier Code Date of Transmission	4AN 6N	SCAC representing the importing carrier. A date in YYMMDD (year, month, day) format representing the date that the inbound transmission to CBP was processed. In most cases the date of processing and the date of transmission will be the same.						
Time of Transmission	6N	A time in HHMMSS (hour, minute, second) 24 hour clock format representing the time that the inbound transmission to CBP was processed. Eastern Standard Time should be reported.						
Total Manifests Read	2N	The total number of manifests (M10 records) read on a given transmission.						
Total Ports Read	3N	The total number of ports (P4 records) read on a single transmission.						
Total Bills Read	5N	The total number of bills (MBL, M11, M21 or M20 segments) read on a single transmission.						
Total House Bills Read Total Amendments Read	5N 5N	Zero filled. This field is not used by CBP. The total number of amendments (M13 records) read on a single transmission						
Total M15 Segment Input	5N	The total number of amendments (M13 records) read on a single transmission.						
Total Bills/Arrivals Rejected	5N	The total number of Bills of Lading (MBL, M11, M13 (D or R), M15, M20 or M21 segments) that were rejected for a single transmission.						
Total Bills/Arrivals Accepted	5N	The total number of Bills of Lading (MBL, M11, M13 (D or R), M15, M20 or M21 segments) that were accepted into the database.						
Total Records Read	5N	The total number of records read on a single inbound transmission. (Excludes the ISA, GS, GE, IEA segments.)						

	Ref.	Data	•		
	Des.	Element	<u>Name</u>		Attributes
M	K301	449	Fixed Format Information	M	1 AN 1/80
			Data in fixed format agreed upon by sende	er and receiver	
	K302	1333	Record Format Code	0	1 ID 1/2
			Code specifying the format of information	l	
Not Used	K303	C001	Composite Unit of Measure	0	1
			To identify a composite unit of measure of use)	(See Figures Appendix for	or examples
Not Used	C00101	355	Unit or Basis for Measurement Code	M	ID 2/2

			Code specifying the units in which a value is being express which a measurement has been taken	sed, or mann	er in
Not Used	C00102	1018	Exponent	O	R 1/15
			Power to which a unit is raised		
Not Used	C00103	649	Multiplier	O	R 1/10
			Value to be used as a multiplier to obtain a new value		
Not Used	C00104	355	Unit or Basis for Measurement Code	O	ID 2/2
			Code specifying the units in which a value is being express which a measurement has been taken	sed, or mann	er in
Not Used	C00105	1018	Exponent	O	R 1/15
			Power to which a unit is raised		
Not Used	C00106	649	Multiplier	O	R 1/10
			Value to be used as a multiplier to obtain a new value		
Not Used	C00107	355	Unit or Basis for Measurement Code	O	ID 2/2
			Code specifying the units in which a value is being express which a measurement has been taken	sed, or mann	er in
Not Used	C00108	1018	Exponent	O	R 1/15
			Power to which a unit is raised		
Not Used	C00109	649	Multiplier	O	R 1/10
			Value to be used as a multiplier to obtain a new value		
Not Used	C00110	355	Unit or Basis for Measurement Code	O	ID 2/2
			Code specifying the units in which a value is being express which a measurement has been taken	sed, or mann	er in
Not Used	C00111	1018	Exponent	O	R 1/15
			Power to which a unit is raised		
Not Used	C00112	649	Multiplier	O	R 1/10
			Value to be used as a multiplier to obtain a new value		
Not Used	C00113	355	Unit or Basis for Measurement Code	O	ID 2/2
			Code specifying the units in which a value is being express which a measurement has been taken	sed, or mann	er in
Not Used	C00114	1018	Exponent	O	R 1/15
			Power to which a unit is raised		
Not Used	C00115	649	Multiplier	O	R 1/10
			Value to be used as a multiplier to obtain a new value		

Segment: **SE** Transaction Set Trailer

Position: 0200

Loop:

Level: Detail Usage: Mandatory

Max Use:

Purpose: To indicate the end of the transaction set and provide the count of the transmitted

segments (including the beginning (ST) and ending (SE) segments)

Syntax Notes: Semantic Notes:

	Ref.	Data				
	Des.	Element	<u>Name</u>	<u>At</u>	trit	<u>outes</u>
M	SE01	96	Number of Included Segments	M	1	N0 1/10
			Total number of segments included in a transaction set including segments	ng ST a	nd S	SE
M	SE02	329	Transaction Set Control Number	M	1	AN 4/9
			Identifying control number that must be unique within the transfunctional group assigned by the originator for a transaction s		set	

Segment: \mathbf{GE} Functional Group Trailer

Position: 0300

Loop:

Level: Detail Usage: Mandatory

Max Use: 1

Purpose: To in

To indicate the end of a functional group and to provide control information

Syntax Notes: Semantic Notes:

1 The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

	Ref.	Data				
	Des.	Element	<u>Name</u>	<u>A</u>	<u>ttrik</u>	<u>outes</u>
M	GE01	97	Number of Transaction Sets Included	M	1	N0 1/6
			Total number of transaction sets included in the functional g	roup or		
			interchange (transmission) group terminated by the trailer con	taining	this	data
			element			
M	GE02	28	Group Control Number Assigned number originated and maintained by the sender	M	1	N0 1/9

Segment: IEA Interchange Control Trailer

Position: 0400

Loop:

Level: Detail Usage: Mandatory

Max Use: 1

Purpose: To define the end of an interchange of zero or more functional groups and interchange-

related control segments

Syntax Notes: Semantic Notes:

	Ref.	Data			
	Des.	Element	<u>Name</u>	<u> </u>	<u>Attributes</u>
M	IEA01	I16	Number of Included Functional Groups	M	1 N0 1/5
			A count of the number of functional groups included in a	n intercha	nge
M	IEA02	I12	Interchange Control Number	M	1 N0 9/9
			A control number assigned by the interchange sender		